

# *The Enviro Meridian Pellet Stove*



Large Freestanding  
Pellet Stoves  
and  
Fireplace Inserts

Meridian with antique body trim and door cover



+



=

Enviro, in partnership with Global ReLeaf International,  
will plant a tree for every Enviro Wood or  
Pellet Stove purchased.



# The Enviro Meridian Pellet Stove

Traditional looks are combined with modern styling, laser cut heavy gauge steel and state-of-the-art heating technology.



Meridian FPI with painted door

## DESIGN FEATURES

- Attractive, durable cast iron brick liner
- Large arched bay door
- Hidden door handle
- Recessed hopper lid handle

## FUNCTION FEATURES

- Hi/Lo thermostat compatible
- Auto/Off thermostat compatible
- Remote control compatible
- Hidden heavy-duty heat exchanger
- Large, full pedestal ash pan (FS model)
- Standard 400-watt ignitor
- Large 55 lb hopper with easy access lid
- Adjustable hopper height (FPI model) from 19" (48.3cm) to 22.75" (57.8cm)
- Covered, easy-to-use controls
- 160 CFM convection fan



Meridian FS with optional 24kt gold accents



Meridian FS with standard painted accents

## OPTIONAL FEATURES

- Antique Copper body trim and/or door cover
- Pewter body trim and/or door cover
- 24kt Gold body trim and/or door cover
- Composite log set
- Zero Clearance kit



Meridian FPI with optional pewter accents

## TRI -MODE CONTROL SYSTEM -

You can operate the Enviro Meridian in three different modes -

1. Manual Mode
2. Hi/Lo Mode
3. Auto/Off Mode - the unit automatically modulates between hi and low with a time delayed auto/off function after 30 minutes on low. When the thermostat calls for heat again, the unit will automatically restart.

## ZERO CLEARANCE RECOMMENDED FRAMING DIMENSIONS -

- Height - 30" (76.2 cm)
- Width - 33" (83.8 cm)
- Depth - 13" (33 cm) Through Wall Venting
- Depth - 23" (58.4 cm) Vertical Venting

## SPECIFICATIONS

	FS	FPI	With ZC kit
Heat Input	12,000 - 45,000 BTU	12,000 - 45,000 BTU	12,000 - 45,000 BTU
EPA Efficiency	75.8%	75.8%	75.8%
EPA Emissions	1.1 g /hour	1.1 g /hour	1.1 g /hour
Weight -	273 lbs (125kg)	263 lbs (121kg)	263 lbs (121kg)
Height -	32.75" (83 cm)	22.75" (57.8 cm)	25.5" (64.8 cm) behind panel
Width -	25" (63.5 cm)	22" (55.8 cm)	20.5" (52 cm) behind panel
Depth -	25" (63.5 cm)	25" (63.5 cm)	11" (27.9 cm) behind panel
Area heated*	2,000 ft <sup>2</sup> (186 m <sup>2</sup> )	2,000 ft <sup>2</sup> (186 m <sup>2</sup> )	2,000 ft <sup>2</sup> (186 m <sup>2</sup> )
Surround (h)	-	30" (76.2 cm)	32" (81.3 cm)
(w)	-	40" (101.6 cm)	38" (96.5 cm)
Oversize (h)	-	33" (83.8 cm)	-
Surround (w)	-	46" (116.8 cm)	-



Meridian FS - Top detail in Antique Copper



Control Panel

\* Figure will vary considerably with floor plan, house layout and heat loss of the house. Due to on-going product development, product appearances and specifications are subject to change without notice. These units must be installed by a qualified dealer. Enviro pellet stoves have been approved for mobile home installations once certain criteria are met. Approved for sale in Canada, the United States and in Europe UL-1482/ULC S627; CSAB366.2M/ULC S628; UL907/UL-127 ULC S610.



Please share and recycle this brochure

